

# SORAA

## Electrical compatibility – A19 120V - North America

### Table of contents

- General compatibility guidelines.....Page 2
- Dimming compatibility.....Page 3-6

## **General compatibility guidelines**

### **Scope**

This document provides the basic guidelines regards electrical compatibility of SORAA 120V A19 lamps.

### **Dimmer Compatibility**

SORAA 120V A19 lamps are made to work with trailing edge (reverse phase) and leading edge (forward phase) phase cut dimmers. However, the use of trailing edge dimmers is preferred and will show in general better behavior.

Dimmer compatibility tables are on pages **3-5**.

The percentages for each dimmer combination are the percentage of light output that we were able to dim down to without seeing any problems like flicker/shimmer. Anything 30% or above is considered not compatible and you will see a “NC” in a grey cell.

There might be a minimum wattage load on the dimmer. If this minimum load is not met, there might be compatibility issues.

### **Maximum number of lamps on a dimmer**

The following need to be considered when determining the amount of lamps on a dimmer.

1. SORAA tests have been carried out with 1 lamp unless stated otherwise.
2. There is a repetitive, very brief current spike the LED will see twice per cycle. This current spike has to be provided by the dimmer, and will affect the recommended fixture load on each dimmer.
3. Ultimately the dimmer manufacturer is the only one with authority to rate their product, but SORAA can give an Engineering estimate.
4. We recommend to use a 5.0 de-rating factor for incandescent/halogen dimmers loaded with our 120V lamps.

**For example for a 500W dimmer it would mean  $500/5 = 100W$  of LED, so an estimated maximum of 9 lamps at 11W.**

### **Disclaimer**

Compatibility tests are conducted by Soraa only as guidance for the user.

All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site.

Results may vary due to variability in component choices and manufacturing processes by dimmer manufacturers.

For more information on the dimmers please find specs on the manufacturer’s website.

## SORAA A19 lamps 120V - DIMMER COMPATIBILITY LIST - North America

Manufacturer	Model	MD #	Dimmer mode	Lamps tested	Dim (%)	Comments
<b>Crestron</b>		DIN-1DIMU4	Reverse Phase	1-3	4%	
<b>ETC</b>	Sensor 3	D20	Forward Phase	6	16%	Tested by dimmer manufacturer (*)
<b>ETC</b>	Sensor 3	ELV10-S	Reverse Phase	6	14%	Tested by dimmer manufacturer (*)
<b>ETC</b>	DRd	D20	Forward Phase	6	35%	Tested by dimmer manufacturer (*)
<b>ETC</b>	DRd	ELV10	Reverse Phase	6	29%	Tested by dimmer manufacturer (*)
<b>ETC</b>	Legacy Unison	D20	Forward Phase	6	48%	Tested by dimmer manufacturer (*)
<b>ETC</b>	Legacy Unison	ELV10	Forward Phase	6	50%	Tested by dimmer manufacturer (*)
<b>ETC</b>	ERP	300W dimmer	Reverse Phase	6	0.11%	Tested by dimmer manufacturer (*)
<b>ETC</b>	Echo	ELVD	Reverse Phase	6	26%	Tested by dimmer manufacturer (*)
<b>Leviton</b>	SureSlide	6633		1-3	13%	(*)
<b>Leviton</b>		A2000	Forward Phase	2	2% (min. 2 lamps)	Min load 40W. Tested by dimmer manufacturer (*)
<b>Leviton</b>		D4206	Forward Phase	2	2% (min. 2 lamps)	Tested by dimmer manufacturer (*)
<b>Leviton</b>	Homekit Wall dimmer	DH6HD-1BZ	Forward Phase	1	5.40%	Tested by dimmer manufacturer (*)
<b>Leviton</b>	Lumina Wall Dimmer	DL6HD-1BZ	Forward Phase	1	0.30%	Tested by dimmer manufacturer (*)
<b>Leviton</b>	WiFi Wall Dimmer	DW6HD-1BZ	Forward Phase	1	0.30%	Tested by dimmer manufacturer (*)
<b>Leviton</b>	Zwave Wall Dimmer	DZ6HD-1BZ	Forward Phase	1	0.30%	Tested by dimmer manufacturer (*)
<b>Leviton</b>	iSERIES	i48E	Forward Phase	2+100W incandescent	4.40%	Min load 100W. Tested load = 2 lamps + 100W incandescent bulb. Tested by dimmer manufacturer (*)

## SORAA A19 lamps 120V - DIMMER COMPATIBILITY LIST - North America

Manufacturer	Model	MD #	Dimmer mode	Lamps tested	Dim (%)	Comments
Leviton	OMNI	110A00-2	Forward Phase	1	0.80%	Tested by dimmer manufacturer (*)
Leviton	OMNI	110A00-2	Reverse Phase	1	20.10%	Tested by dimmer manufacturer (*)
Leviton	Power Extender	PE100-10W	Forward Phase	2	2.1% (min. 2 lamps)	Tested by dimmer manufacturer (*)
Leviton	Power Extender	PE400-10W	Reverse Phase	2	10.3% (min. 2 lamps)	Tested by dimmer manufacturer (*)
Leviton	RENOIR II	AWSMT-EBW	Reverse Phase	2+60W incandescent	0.40%	Min load 64W. Tested load = 2 lamps + 60W incandescent bulb. Tested by dimmer manufacturer (*)
Leviton	RENOIR II	AWSMT-MBW	Forward Phase	2+60W incandescent	2.70%	Min load 64W. Tested load = 2 lamps + 60W incandescent bulb. Tested by dimmer manufacturer (*)
Lutron	Caseta	PD-5NE-XX	Reverse Phase	1-3	19%	(*)
Lutron	Diva	DVELV-300P	Reverse Phase	1-3	7%	
Lutron	Diva	DVLV-600P	Forward Phase	1-3	19%	
Lutron	Diva	DVCL-153P	Forward Phase	1-3	NC	(*)
Lutron	Grafik Eye QS	QSGR	Forward Phase	1-3	27%	(*)
Lutron	Grafik Eye QS	QSGR + PHP module	Reverse Phase	1-3	2%	
Lutron	Maestro	MACL-153M	Forward Phase	1-3	21%	(*)
Lutron	Radio RA2	RRD-6NA	Reverse Phase	1-3	19%	(*)
Lutron	Skylark	SLV-600P	Forward Phase	1-3	16%	
Lutron	Skylark	SELV-300P	Reverse Phase	1-3	8%	
Lutron	Spacer	SPSELV-600	Reverse Phase	1	12%	
Marlin	Stellar	RMS 4	Reverse Phase	1	4%	

## SORAA A19 lamps 120V - DIMMER COMPATIBILITY LIST - North America

### Notes:

Compatibility tests are conducted by Soraa (unless stated otherwise) only as guidance for the user

All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site

Results may vary due to variability in component choices and manufacturing processes by the dimmer manufacturer

Regards compatibility tests conducted by dimmer manufacturer, please contact the dimmer manufacturer or Soraa for more details and/or reports.

(\*) Test results with this dimmer added to the compatibility list as of Revision 18Q3

--%	Dims to < 20% (of the measured light output)
--%	Dims to 20-30% (of the measured light output)
NC	Not compatible (or dims to >30%)
Blank cell	Not tested