



## Electrical compatibility – Brilliant HL MR16 12V GU5.3 7.5W & 9W lamps - International

### Table of contents

- General compatibility guidelines.....Page 2
- Transformer compatibility.....Page 3-6
- Dimming compatibility.....Page 7-10
  - Soraa Optima Phase-cut electronic transformer.....Page 7
  - Other electronic transformers with phase-cut large dimming systems.....Page 8
  - Other controls (DALI, 0-10V).....Page 8
  - Other electronic transformers with small phase-cut dimmers.....Page 9

### Scope

This document provides the basic guidelines regards electrical compatibility of SORAA 12V MR16 lamps and compatibility tables for transformers and dimmers.

### Transformer Compatibility

SORAA 12V MR16 lamps are made to work with 12V AC magnetic (MLV) and electronic (ELV) transformers and 12V DC transformers. Transformer compatibility tables are on this document too. If multiple lamps are installed on one transformer, they need to be connected in parallel. They cannot be installed in series.

- 12V AC Magnetic transformers and 12V DC transformers are in general compatible.
- 12V AC Electronic transformers generally have a minimum load, and SORAA recommends using only transformers that have been tested and found compatible. In general we recommend to use transformers with very little or no minimum load (0W). If your transformer is not in the compatibility tables below, it does not mean it is incompatible, but it means that we have not tested it to date, please contact [techsupport@soraa.com](mailto:techsupport@soraa.com) for guidance.

### Dimmer Compatibility

SORAA 12V MR16 lamps are made to work with trailing edge (reverse phase) and leading edge (forward phase) phase cut dimmers.

Electronic dimmable transformers need trailing edge dimmers, while Magnetic transformers need leading edge dimmers. Dimmer compatibility tables are on pages 8-15.

Along the top of the dimmer compatibility tables you will see the different dimmers that we have tested, and along the left side of the chart you will see the different transformers we tested. The percentages for each transformer/dimmer combination are the percentage of light output that we were able to dim down to without seeing any problems like flicker/shimmer. Anything 30% or above is considered not compatible and you will see a “NC” in a grey cell. There might be a minimum wattage load on the transformer/dimmer. If this minimum load is not met, there might be compatibility issues.

### Maximum number of lamps on a dimmer/transformer

The following need to be considered when determining the amount of lamps on a dimmer/transformer.

1. SORAA tests have been carried out with 1 lamp unless stated otherwise.
2. There is a repetitive, very brief current spike the LED lamp will see twice per cycle. This current spike has to be provided by the transformer and/or dimmer, and will affect the recommended lamp load on each transformer or dimmer.
3. Ultimately the transformer/dimmer manufacturer is the only one with authority to rate their product, but SORAA can give an Engineering estimate.
4. We have added the maximum amount of MR16 lamps we recommend for each transformer in the transformer compatibility tables.
5. For dimmers, we recommend to use a 2.0 de-rating factor for leading edge dimmers with magnetic transformers; and a 4.0 de-rating factor for incandescent/halogen trailing edge dimmers driving Low Voltage lamps on electronic transformers.

**For example for a 500W leading edge dimmer it would mean  $500/2=250W$  of LED, so an estimated maximum of 33 lamps 7.5W.**

**For example for a 400W trailing edge dimmer it would mean  $400/4=100W$  of LED, so an estimated maximum of 13 lamps 7.5W.**

### Distance between transformer and lamp(s)

- 12V AC Magnetic transformers and 12V DC transformers do not have a limitation regards the maximum length of the wires between transformer and lamp. Only the voltage drop has to be taken into account (losses because of the inner resistance of the conductors).
- 12V AC Electronic transformers have a limitation in the length of the wires between transformer and lamp(s). This length is usually stated by the transformer manufacturer on its specs or on the transformer itself, and generally it is limited to 2 meters (6 feet).

### Disclaimer

Compatibility tests are conducted by Soraa only as guidance for the user. All tests are conducted under bench conditions; results may differ from test results depending on conditions at the application site. Results may vary due to variability in component choices and manufacturing processes by the transformer and dimmer manufacturers. For more information on the dimmers/transformers, please find specs on the manufacturer’s website.

# SORAA BRILLIANT HL MR16 12V 7.5W & 9W - TRANSFORMER COMPATIBILITY LIST - International

**PASS** - The transformer supports one or more lamps up to the maximum wattage;

**NC** - SORAA does not recommend this transformer for use with its lamps;

**2 Lamp Min** - The transformer supports two or more lamps upto the maximum lamp wattage limit;

**3 Lamp Min** - The transformer supports three or more lamps upto the maximum lamp wattage limit

Brand	Model	Wattage	Country	Transformer Type	7.5W		9W	Maximum Number of 7.5-Watt Lamps per Transformer	Maximum Number of 9-Watt Lamps per Transformer
International					Free Air or Open Fixture	Enclosed Fixture	Free Air or Open Fixture		
ABB	Speedy105 ETR 105-230/12KF	105	Germany	Electronic	2 lamp min	2 lamp min	2 lamp min	9	7
AcTec	Mini60 Series III (*)	60	HK/China	Electronic	NC	NC	NC	NC	NC
AcTec	Ultra 70	70	HK/China	Electronic	PASS	PASS	PASS	5	4
Beyond Illumination	BY12T-1W12V-1 (*)	12	EU, Asia	Electronic/DC	PASS	PASS	PASS	1	1
BLV	45600101	60	Germany	Electronic	PASS	PASS	PASS	4	3
BLV	45600201	105	Germany	Electronic	PASS	PASS	PASS	8	6
ECOPAC	ELED-80-12T	80	EU	Electronic/DC	NC	NC	NC	NC	NC
EldoLED	LINEARdrive 100A	100	EU	Electronic/DC	NC	NC	NC	NC	NC
Euchips	EUP12D-1H12V-0 (*)	12	EU, Asia	Electronic/DC	PASS	PASS	PASS	1	1
Euchips	EUP12A-1M12V-1 (*)	12	EU, Asia	Electronic/DC	PASS	PASS	PASS	1	1
Euchips	EUP12T-1W12V-1 (*)	12	EU, Asia	Electronic/DC	PASS	PASS	PASS	1	1
Fulham	T1M1UNV012V-20L	20	EU-Asia	Electronic/DC	PASS	PASS	PASS	1	1
Fulham	T1M1UNV012V-60L	60	EU-Asia	Electronic/DC	PASS	PASS	PASS	5	4
Govena	YT50	50	EU	Electronic	PASS	PASS	PASS	3	3
Govena	YT60	60	EU	Electronic	PASS	PASS	PASS	4	3
Hatch	RS12-60-230M-LED	60	EU	Electronic	PASS	PASS	PASS	5	4
LCI	Code 1700123 (*)	10	EU	Electronic	NC	NC	NC	NC	NC
LCI	Code 1734014 (*)	150	EU	Electronic/DC	PASS	PASS	PASS	13	11
LCI	ET3-60C	60	EU	Electronic	PASS	PASS	PASS	4	3
Lichtech	LET75	75	Italy/ Spain/ UK	Electronic	PASS	PASS	PASS	4	4
Light-Dept	Ultra 70	70	HK/China	Electronic	PASS	PASS	PASS	5	4
LTSYS	DALI-36-12-F1P1	36	APAC	Electronic/DC	NC	NC	NC	NC	NC
Mean Well	LPV-20-12	20	Asia	Electronic/DC	PASS	PASS	PASS	1	1

# SORAA BRILLIANT HL MR16 12V 7.5W & 9W - TRANSFORMER COMPATIBILITY LIST - International

**PASS** - The transformer supports one or more lamps up to the maximum wattage;

**NC** - SORAA does not recommend this transformer for use with its lamps;

**2 Lamp Min** - The transformer supports two or more lamps upto the maximum lamp wattage limit;

**3 Lamp Min** - The transformer supports three or more lamps upto the maximum lamp wattage limit

Brand	Model	Wattage	Country	Transformer Type	7.5W		9W	Maximum Number of 7.5-Watt Lamps per Transformer	Maximum Number of 9-Watt Lamps per Transformer
International					Free Air or Open Fixture	Enclosed Fixture	Free Air or Open Fixture		
Mode Lighting	MOE-050-D-240	50	UK	Electronic	PASS	PASS	PASS	3	3
Mode Lighting	ET-040-PL-230-RD (Puma LED)	40	EU	Electronic	PASS	PASS	PASS	3	2
Multiload	VMD300/12	300	UK	Magnetic	NC	NC	NC	NC	NC
Niko	320-00101 70W	70	EU	Electronic	PASS	PASS	PASS	5	4
OSRAM	ET-A 60 / 220-240	60	HK/China	Electronic	NC	NC	NC	NC	NC
OSRAM	ET-LED 30 / 220-240	30	HK/China	Electronic	PASS	PASS	PASS	2	1
OSRAM	ET-P 60	60	HK/China	Electronic	2 lamp min	2 lamp min	2 lamp min	4	3
OSRAM	ET-PARROT 70 / 220-240 I	70	EU	Electronic	PASS	PASS	PASS	5	4
OSRAM	ET-REDBACK 40VA / 230-240	40	Australia	Electronic	NC	NC	NC	NC	NC
OSRAM	ET-REDBACK 60VA / 230-240	60	Australia	Electronic	NC	NC	NC	NC	NC
OSRAM	Hti DALI 105 / 230-240 DIM	105	France /Germany	Electronic	NC	NC	NC	NC	NC
OSRAM	HTM 70 / 230-240	70	EU	Electronic	PASS	PASS	PASS	2	2
OSRAM	HTM 105 / 230-240	105	EU, CN	Electronic	PASS	PASS	PASS	7	6
OSRAM	HTM 150 / 230-241	150	EU, ME	Electronic	2 lamp min	2 lamp min	2 lamp min	11	9
PHILIPS	CERTALINE 60W	60	EU	Electronic	2 lamp min	2 lamp min	2 lamp min	5	4
PHILIPS	CERTALINE 105W	105	Italy/Spain	Electronic	2 lamp min	2 lamp min	2 lamp min	10	8
PHILIPS	CERTALINE 150W	150	Italy/Spain	Electronic	PASS	PASS	PASS	10	8
PHILIPS	ET E-60	60	HK/China	Electronic	2 lamp min	2 lamp min	2 lamp min	5	4
PHILIPS	ET-E 10 LED 220-240V	10	HK/China	Electronic	NC	NC	NC	NC	NC
PHILIPS	ET-S 15 LED	15	EU, CN	Electronic	PASS	PASS	PASS	1	1
PHILIPS	ET-S 30 LED	30	EU, CN	Electronic	NC	NC	NC		
PHILIPS	ET-S 60 220-240	60	EU, Asia	Electronic	PASS	PASS	PASS	5	4
PHILIPS	Primaline 70 230-239	70	EU, CN	Electronic	2 lamp min	2 lamp min	2 lamp min	5	4
PHILIPS	Primaline 105 230-240	105	EU, CN	Electronic	3 lamp min	3 lamp min	2 lamp min	7	6

# SORAA BRILLIANT HL MR16 12V 7.5W & 9W - TRANSFORMER COMPATIBILITY LIST - International

**PASS** - The transformer supports one or more lamps up to the maximum wattage;

**NC** - SORAA does not recommend this transformer for use with its lamps;

**2 Lamp Min** - The transformer supports two or more lamps upto the maximum lamp wattage limit;

**3 Lamp Min** - The transformer supports three or more lamps upto the maximum lamp wattage limit

Brand	Model	Wattage	Country	Transformer Type	7.5W		9W	Maximum Number of 7.5-Watt Lamps per Transformer	Maximum Number of 9-Watt Lamps per Transformer
International					Free Air or Open Fixture	Enclosed Fixture	Free Air or Open Fixture		
Relco	ICE 60 PFS TH	60	Italy/Spain	Electronic	2 lamp min	2 lamp min	2 lamp min	5	4
Relco	ICE 105 PFS TH	105	Italy/Spain	Electronic	NC	NC	NC	NC	NC
<b>SORAA</b>	<b>Optima TCVW-P-12-600-70-01-S3</b>	70	EU,Asia, Australia	Electronic	PASS	PASS	PASS	5	4
TCI	DC JOLLY DALI (cod.123424)	10	EU	Electronic/DC	NC	NC	NC	NC	NC
TCI	MW 70 LED(Ref. 119772)	70	Italy/Spain	Electronic	NC	NC	NC	NC	NC
TCI	Round 50(Ref. 119649)	50	EU/ME	Electronic	2 lamp min	2 lamp min	2 lamp min	4	3
Tridonic	LCBU 25W 12V BASIC phase-cut SR	25	EU, Turkey	Electronic/DC	NC	NC	NC	NC	NC
Truelux	DA12VPWM	20	EU, ME, Asia	Electronic/DC	PASS	PASS	PASS	2	1
Truelux	DA12VPWM10	10	EU, ME, Asia	Electronic/DC	PASS	PASS	PASS	1	1
Truelux	AN12VPWM	20	EU, ME, Asia	Electronic/DC	PASS	PASS	PASS	2	1
Truelux	AN12VPWM10	10	EU, ME, Asia	Electronic/DC	PASS	PASS	PASS	1	1
Truelux	PH12VLN	50	EU	Electronic	PASS	PASS	PASS	3	3
Varilight	YT50LZ	50	UK	Electronic	PASS	PASS	PASS	4	3
ABB Stotz	SI-TR200	200	EU	Magnetic	PASS	PASS	PASS	19	15
B&T	ALV 200 NM	200	EU	Magnetic	PASS	PASS	PASS	19	15
ETE	MV0300P1S3	300	EU	Magnetic	PASS	PASS	PASS	28	23
GATA	T50/209.23	50	Thailand	Magnetic	PASS	PASS	PASS	4	3
Houben	SICHERHEITSFAFO EKT V1 200	200	EU	Magnetic	PASS	PASS	PASS	19	15
Light Ideas	T-UNO/20/LI/00	20	EU	Magnetic	PASS	PASS	PASS	1	1
Light Scape Projects	n. 121-077 50W	50	EU	Magnetic	PASS	PASS	PASS	4	3
Noratel	LF84A-22012-GS	105	Nordic	Magnetic	PASS	PASS	PASS	10	8
Vossloh Schwabe	STR 50/12.342	50	EU	Magnetic	PASS	PASS	PASS	4	3

## SORAA Brilliant HL MR16 12V 7.5W & 9W - TRANSFORMER COMPATIBILITY LIST - International

### Notes:

- Compatibility tests are conducted by Soraa under bench conditions as guidance for the user; results at the application site may differ due to variability in usage conditions or in transformer components/manufacturing
- If the transformer's minimum wattage is not met, the lamp may only operate under nominal conditions (nominal line voltage and thermal conditions where the lamp is at full power).
- If the transformer is not listed, please consult with Soraa before making recommendations to the end customer
- Above table is for applications where no dimmer is used. If a dimmer is used, the user should consult the Dimmer/Transformer table, or contact Soraa if their desired combination is not listed.
- (\*) This transformer added to the compatibility list as of this Revision

## SORAA Optima 230V Electronic 12V transformer with 12V Soraa MR16 Brilliant HL lamps - DIMMER COMPATIBILITY LIST

Dimmer Manufacturer	Dimmer family	Dimmer model number	Dimming mode	Number of transformers tested per dimmer	Number of lamps per transformer	Dim (%)	Comments
Busch		6523 U-102	Trailing	3	1	14%	Limited by dimmer travel
Feller		40200.LED.FMI.61	Trailing	3	1	8%	
Gira		238500 / I01	Adaptive-TE	3	1	15%	Limited by dimmer travel
Helvar	Digidim	454	Trailing	3, 5	1	5%	
Jung		1224 LED UDE	Trailing	3, 5	1	6%	Limited by dimmer travel
LCI		#1770100	Trailing	1, 10	1	0%	(*)
Lutron	Grafik Eye QS + Interface	PHPM with Grafik Eye QS main unit	Adaptive-TE	3, 5	1	6%	Limited by dimmer travel
Lutron	Homeworks QS Energy Savr Node QS (for Quantum and QS systems)	QSNE-4A-D (Gen2) / LQSE-4A-D (Gen2)	Trailing	3, 5	1	6%	
Philips Dynalite		DGLEDM401	Trailing	3, 5	1	13%	Limited by dimmer travel
Varilight	V-PRO	JQP401W	Trailing	3, 5	1	8%	Limited by dimmer travel

**SORAA BRILLIANT H.L. MR16 12V 7.5W & 9W - DIMMING COMPATIBILITY LIST - International**

Transformer manufacturer ↓	Transformer model ↓	Transf. type ↓	Number of lamps per transformer ←	Dimmer →	Large multi-channel system, DIN-rail mounted dimmers							
					ABB 6586-500	Dynalite DGLDM401	Helvar Digidim 452	Helvar Digidim 454	Honeywell Inncomm H454.F.CE	Lutron Energi Savr Node QS QSNE-4A-D	Lutron Grafik Eye QS with ELV Interface QSGRK-3PCE + PHPM	Lutron Remote Power Module RPM-4A-230
				Dimming phase →	Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge
<b>BLV</b>	Luxia 60W (nr. 45600101)	ELV	1			10%		5%		5%	5%	
<b>Euchips</b>	EUP12T-1W12V-1 (*)	ELV	1		NC	NC	17%	20%	10%	15%		30%
<b>Govena</b>	YT60	ELV	1			10%		5%		5%	5%	
<b>Osram</b>	ET-LED 30	ELV	1			9%		5%		6%	4%	

Transformer manufacturer ↓	Transformer model ↓	Transf. type ↓	Number of lamps per transformer ←	Dimming protocol →	DALI	0-10V
<b>Euchips</b>	EUP12D-1H12V-0 (*)	ELV / DC	1		12%	
<b>Euchips</b>	EUP12A-1M12V-1 (*)	ELV / DC	1			14%
<b>Multiload</b>	LEDixia (*)	PWM (plus extra DC power supply)	1-8			1%



**SORAA BRILLIANT H.L. MR16 12V 7.5W & 9W - DIMMING COMPATIBILITY LIST - International**

Transformer manufacturer ↓	Transformer model ↓	Transf. type ↓	← Number of lamps per transformer	Dimmer →	Small, wall mounted dimmers, etc							
				Dimming phase →	Bticino NT4411N	Busch 6523 U-102	Feller 40200.LED.FMI. 61	GIRA 238500 / I01	Jung 1224 LED UDE	Legrand Arteor Cat nr. 5 722 39	Lutron RA2 select RRK-R25NE-240	Varilight V-PRO JQP401W
					Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge	Trailing edge
<b>BLV</b>	Luxia 60W (nr. 45600101)	ELV	1			14%	9%		6%			8%
<b>Euchips</b>	EUP12T-1W12V-1 (*)	ELV	1		8%					30%	NC	
<b>Europole</b>	OPTIMO 4-60VA	ELV	1			9%						
<b>Govena</b>	YT50	ELV	1				11%	14%				
<b>Govena</b>	YT60	ELV	1			14%	9%		6%			8%
<b>LCI</b>	ET 3-60 C	ELV	1			9%						
<b>Lightech</b>	LET75	ELV	1			10%	7%					
<b>Osram</b>	ET-LED 30	ELV	1						6%			11%
<b>Osram Halotronics</b>	HTM 70	ELV	1				6%					
<b>Osram Halotronics</b>	HTM 105	ELV	1				9%					
<b>Philips</b>	ET-S 15 LED	ELV	1				7%					
<b>Truelux</b>	PH12VLN	ELV	1				11%	14%				
<b>Varilight</b>	YT50	ELV	1				11%	14%				
<b>Varilight</b>	YT50LZ	ELV	1				6%					

## SORAA Brilliant HL MR16 12V 7.5W & 9W – Dimmer COMPATIBILITY LIST - International

### Notes:

- Compatibility tests are conducted by Soraa (unless stated otherwise) under bench conditions as guidance for the user.
- Regards compatibility tests conducted by dimmer / transformer manufacturer, please contact Soraa or the manufacturer for more details and/or reports.
- Results at the application site may differ due to variability in usage conditions or in dimmer or transformer components/manufacturing.
- If the transformer's minimum wattage is not met, the lamp may only operate under nominal conditions (nominal line voltage and thermal conditions where the lamp is at full power).
- Transformer maximum load listed in the transformer compatibility table should not be exceeded.
- If the dimmer and/or transformer is not listed, please consult with Soraa before making recommendations to the end customer.
- (\*) One or more test results with this transformer added to the compatibility list as of this Revision

--%	Dims to < 20% (of the measured light output)
--%	Dims to 20-30% (of the measured light output)
NC	Not compatible (or dims to >30%)
Blank cell	Not tested