SORAA arc

• Read all instructions carefully before installing.

• Ensure that power is off on the main panel before starting installation or performing any maintenance.

• Do not install this lighting system in a wet location.

• Do not install any fixture closer than 6 inches from any curtain or combustible material.

• Make sure all screws are properly tightened.

• Supply and install correct Junction Box and Device Cover as indicated at right before final installation of luminaire.

Surface Mounting


Step 1. Install J-box in ceiling. Pull wires through ceiling opening. Install trim ring and attach to J-box with screws (Fig. 1).

Step 2. Attach luminaire to trim ring safety harness with carabiner clip (Fig. 2).

Step 3. Connect black and white line voltage and green ground wires from luminaire to line voltage and ground wires from J-box, and connect dimming wires from ceiling to corresponding wires from luminaire if required (Fig. 3). Driver accepts 120VAC input.

Step 4. Insert luminaire into trim ring (Fig. 4). Push up and turn luminaire clockwise (Fig. 5) until you hear a distinct click indicating that tabs are locked into position as shown in Fig. 6.

YOU WILL NEED:






(Included in Box)

(Included in Box)

Trim Ring

Luminaire

(38mm) **c)** or 2" (51mm)



4"(102mm)

4" Junction box 1-1/2" or 2" deep (Not Included in Box)

